



Bona Freshen Up

WOOD FLOOR MAINTENANCE

Waterborne coating for periodic maintenance



Bona Freshen Up is a ready-to-use maintenance coating for the periodic maintenance and protection of lacquered wood floors. Based entirely on a polyurethane dispersion it creates a durable wear layer equipped to take on foot traffic in both domestic and commercial areas. Produces a high gloss finish, giving new lustre to dull floors. Formulated without the addition of waxes making it possible to overcoat with professional lacquer if need be.

- Specifically designed for lacquered wood floors
- Premium polyurethane product base
- Meets EN 14904:2006 and DIN 18032:2 for slip resistance.

TECHNICAL DATA

Product base:	Waterborne polyurethane dispersion
Sheen:	Hi-gloss
Dilution:	Do not dilute, product is ready-to-use
Drying time:	1-2 hours (20°C/60% RH)
Application tools:	Bona Applicator Pad
Coverage:	~50 m ² /litre
Cleaning:	Clean tools in soap and water. Dried stains can be removed with Bona Remover or acetone.
Shelf life:	2 years, from date of production, in unopened original container
Storage/Transport:	The temperature must not fall below +5°C or exceed +30°C during storage and transport.
Disposal:	Waste and emptied containers should be handled in accordance with local regulations.
Pack size:	10 x 1 liter (50 boxes per pallet) 3 x 5 liters (44 boxes per pallet)

Additional detailed information is noted in the appropriate Safety Data Sheet.

2023-09-19
This data sheet replaces all previous versions
please check bona.com to ensure that you have
the latest version.



Bona Freshen Up

WOOD FLOOR MAINTENANCE

Waterborne coating for periodic maintenance

PREPARATION

Remove loose dirt and grit from your floor. Depending on the degree of soiling, mix a suitable solution of Bona Cleaner or Bona Deep Clean Solution and wet clean the floor thoroughly. Observe that any remaining dirt will become trapped in the coating and cannot be removed afterwards. Let floor dry completely.

Do not use Bona Freshen Up on any floor that has been waxed or oiled as residues from these materials may disrupt the adhesion to the surface. It is recommended to always test the adhesion to the surface and check for desired results prior to using Bona Freshen Up.

APPLICATION

1. Shake container thoroughly before use. Apply Bona Freshen Up in a 3-4 cm wide wavy line on a 3 m² section of the floor and without delay, spread the product using a flat polish application pad. For best results, maintain a thin consistent coat.
2. Without adding more product, smooth out the section by moving the applicator with the grain of the wood.
3. Continue with next section and then continue section by section until the entire floor has been treated.
4. If a second application is required, allow at least 2 hours between applications.
5. The floor can be walked on after 1 hour but avoid heavy traffic and the replacement of furniture/rugs for at least 12 hours.

To achieve a uniform appearance, it is advised to always treat the entire surface.

MAINTENANCE

Wet cleaning of the floor may be resumed after three days. For regular cleaning use Bona Cleaner. Do not use strongly alkaline cleaning agents as they may damage the floor or remove the protective coating of Bona Freshen Up. In contrast to floors treated with polish, wax or similar material, a floor maintained with Bona Freshen Up can still be overcoated with professional lacquer.

TIPS

- When smoothing out the product, keep the applicator pad flat to the surface and apply from wall-to-wall. Avoid lifting the applicator along the way as this produces bubbles.
- Do not work into areas starting to dry as this may produce streaking.
- If applying multiple layers of Bona Freshen Up, do not rush the drying time between coats. There is a risk of dissolving previous layers.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and extensive testing but makes no claim to be complete. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice from Bona before use. Bona can only guarantee its products and not the construction as a whole. Observe recommendations from flooring manufacturer and the provisions of relevant standards.